Instalar OpenWebMail en Slackware64 14.0

Este artículo explica cómo instalar OpenWebmail y configurarlo para que pueda acceder a su buzón utilizando una interfaz web desde cualquier lugar con acceso a Internet y un navegador web disponible.
Estas instrucciones se probaron en el sistema operativo Slackware64 14.0 de 64 bits y en la última versión de openwebmail-current.tar.gz (en realidad, la versión 2.53)
Esto significa que usted está configurado y ejecutando el servidor web Apache y el servidor de correo Sendmail.

Instalar bibliotecas y paquetes necesarios

Utilizando CPAN a través de CPAN.pm:

```
perl -MCPAN -e shell                    [as root]
o conf prerequisites_policy ask
```

entonces:

```
install CGI
install Compress:Zlib
install Convert::ASN1
install Digest
install Digest::MD5
install IO::Socket::SSL
install MIME::Base64
install Net::SSLeay
install Text::Iconv

quit
```

Instalar OpenWebMail

1. Primero, descargue la última versión de openwebmail: openwebmail-current.tar.gz
2. Cree un directorio donde lo desee, que diga “ `/ ADISKS / openwebm_inst` ” y mueva el archivo descargado “ `openwebmail-current.tar.gz` ” a ese directorio.
3. Extraer todos los archivos usando el comando.

   ```
   tar -zxvBpf openwebmail-current.tar.gz
   ```

   Use la opción “tar” con “-zxvBpf”, debido a los permisos de archivos extraños dentro de ese archivo. Traté de descomprimirlo a través de las herramientas de archivo integradas midnight comander, y el script *wrapsuid* no funcionaría debido a esto …

4. Mueva el directorio extraído “ `cgi-bin/openwebmail` ” a “ `/var/www/cgi-bin/openwebmail` ”
5. Mueva el directorio extraído “ `data/openwebmail` ” a *DocumentRoot* de su servidor web (en una configuración de Apache predeterminada, que será “ `/var/www/openwebmail` ”)
6. Cambie el directorio a “ `/var/www/openwebmail` ”, elimine el archivo `index.html` y ejecute el comando

```
ln -s redirect.html index.html
```

7. Cambie el directorio a “ `/var/www/cgi-bin/openwebmail` ” y ejecute el comando

```
perl misc/tools/wrapsuid/wrapsuid.pl /var/www/cgi-bin/openwebmail
```

Deberías ver el siguiente resultado:

```
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-folder.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-main.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-read.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-send.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-cal.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-webdisk.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-advsearch.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-abook.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-viewatt.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-vdomain.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-saprefs.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-prefs.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-tool.pl
Fixing /tmp/openwebmail/cgi-bin/openwebmail/openwebmail-spell.pl
```

8. Then go to “`/var/www/cgi-bin/openwebmail/etc`” and edit the configuration files:
    1. Change “`openwebmail.conf`” according to:

```
domainnames             auto
auth_module             auth_unix.pl
mailspooldir            /var/spool/mail
ow_cgidir               /var/www/cgi-bin/openwebmail
ow_cgiurl               /cgi-bin/openwebmail
ow_htmldir              /var/www/openwebmail
ow_htmlurl              /
logfile                 /var/log/openwebmail.log
```

    2. Cambie el directorio a “ `/var/www/cgi-bin/openwebmail/etc/defaults` ”, edite `auth_unix conf` para que se convierta en

```
passwdfile_plaintext    /etc/passwd
passwdfile_encrypted    /etc/shadow
passwdmkdb              none
```

    3. En el directorio “ `/var/www/cgi-bin/openwebmail/etc/defaults` ”, edite

`db.conf` de la siguiente manera:

```
dbm_ext                 .db
dbmopen_ext             .db
dbmopen_haslock         no
```

4. Luego, cambie el directorio a “ `/var/www/cgi-bin/openwebmail` ” y ejecute

```
./openwebmail-tool.pl --init
```

9. Después de eso, vaya a “ `/var/www/cgi-bin/openwebmail` ”, verifique que haya archivos que empiecen con un punto (como “ `.openwebmail.pl` ”) y nombres de archivos de estilo antiguo (como “ `openwebmail.pl)` ”. Establezca el *suid* bit para estos scripts:

```
chmod u+s openwebmail*.pl
chmod u+s .openwebmail*.pl
```

Configuración adicional de Apache

- Agregue una opción AddHandler cgi-script .cgi .pl en `/etc/httpd/httpd.conf` en la sección “Directory /srv/httpd /” httpd.conf como ser:

```
ServerRoot "/usr"
Listen 80

LoadModule authn_file_module lib64/httpd/modules/mod_authn_file.so
LoadModule authn_core_module lib64/httpd/modules/mod_authn_core.so
LoadModule authz_host_module lib64/httpd/modules/mod_authz_host.so
LoadModule authz_groupfile_module
lib64/httpd/modules/mod_authz_groupfile.so
LoadModule authz_user_module lib64/httpd/modules/mod_authz_user.so
LoadModule authz_core_module lib64/httpd/modules/mod_authz_core.so
LoadModule access_compat_module
lib64/httpd/modules/mod_access_compat.so
LoadModule auth_basic_module lib64/httpd/modules/mod_auth_basic.so
LoadModule reqtimeout_module lib64/httpd/modules/mod_reqtimeout.so
LoadModule filter_module lib64/httpd/modules/mod_filter.so
LoadModule mime_module lib64/httpd/modules/mod_mime.so
LoadModule log_config_module lib64/httpd/modules/mod_log_config.so
LoadModule env_module lib64/httpd/modules/mod_env.so
LoadModule headers_module lib64/httpd/modules/mod_headers.so
LoadModule setenvif_module lib64/httpd/modules/mod_setenvif.so
LoadModule version_module lib64/httpd/modules/mod_version.so
LoadModule proxy_module lib64/httpd/modules/mod_proxy.so
LoadModule proxy_connect_module
lib64/httpd/modules/mod_proxy_connect.so
LoadModule proxy_ftp_module lib64/httpd/modules/mod_proxy_ftp.so
LoadModule proxy_http_module lib64/httpd/modules/mod_proxy_http.so
LoadModule proxy_fcgi_module lib64/httpd/modules/mod_proxy_fcgi.so
```

```
LoadModule proxy_scgi_module lib64/httpd/modules/mod_proxy_scgi.so
LoadModule proxy_ajp_module lib64/httpd/modules/mod_proxy_ajp.so
LoadModule proxy_express_module
lib64/httpd/modules/mod_proxy_express.so
LoadModule lbmethod_byrequests_module
lib64/httpd/modules/mod_lbmethod_byrequests.so
LoadModule lbmethod_bytraffic_module
lib64/httpd/modules/mod_lbmethod_bytraffic.so
LoadModule lbmethod_bybusyness_module
lib64/httpd/modules/mod_lbmethod_bybusyness.so
LoadModule mpm_event_module lib64/httpd/modules/mod_mpm_event.so
LoadModule unixd_module lib64/httpd/modules/mod_unixd.so
LoadModule status_module lib64/httpd/modules/mod_status.so
LoadModule autoindex_module lib64/httpd/modules/mod_autoindex.so
##openwebmail!
LoadModule cgi_module lib64/httpd/modules/mod_cgi.so
LoadModule dir_module lib64/httpd/modules/mod_dir.so
LoadModule alias_module lib64/httpd/modules/mod_alias.so

<IfModule unixd_module>
User apache
Group apache

</IfModule>

# 'Main' server configuration
#
# The directives in this section set up the values used by the 'main'
# server, which responds to any requests that aren't handled by a
# <VirtualHost> definition.  These values also provide defaults for
# any <VirtualHost> containers you may define later in the file.
ServerAdmin webmaster@sten.lv

ServerName elephant.org


<Directory />
    AllowOverride None
</Directory>

DocumentRoot "/srv/httpd/"
<Directory "/srv/httpd/">

    Options Indexes FollowSymLinks Includes MultiViews ExecCGI

    AllowOverride All
    #None

    #
    # Controls who can get stuff from this server.
```

```
    #
##    Require all granted
Order allow,deny
Allow from all
###Need! otherwise "save as binary...." appear...
AddHandler cgi-script .cgi .pl

</Directory>

#
# DirectoryIndex: sets the file that Apache will serve if a directory
# is requested.
#
<IfModule dir_module>
    DirectoryIndex index.html index.shtml index.php
</IfModule>

#
# The following lines prevent .htaccess and .htpasswd files from being
# viewed by Web clients.
#
<Files ".ht*">
    Require all denied
</Files>



ErrorLog "/var/log/httpd/error_log"

LogLevel warn

<IfModule log_config_module>

    LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-
Agent}i\"" combined
    LogFormat "%h %l %u %t \"%r\" %>s %b" common

    <IfModule logio_module>
      # You need to enable mod_logio.c to use %I and %O
      LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-
Agent}i\" %I %O" combinedio
    </IfModule>

    #
    ##CustomLog "/var/log/httpd/access_log" common

    #
    CustomLog "/var/log/httpd/access_log" combined
</IfModule>

<IfModule alias_module>
```

```
  #
    ScriptAlias /cgi-bin/ "/srv/httpd/cgi-bin/"

</IfModule>

<IfModule cgid_module>
    #
#    Scriptsock cgisock
</IfModule>

#
# "/srv/httpd/cgi-bin" should be changed to whatever your ScriptAliased
# CGI directory exists, if you have that configured.
#
##<Directory "/srv/httpd/cgi-bin">
##    AllowOverride None
##    Options None
##    Require all granted
##</Directory>
#for openwebmail
<Directory "/srv/httpd/cgi-bin">
    AllowOverride All
    Options ExecCGI
    Order Allow,deny
    Allow from all
</Directory>


<IfModule mime_module>
    #
    TypesConfig /etc/httpd/mime.types

    #
    AddType application/x-compress .Z
    AddType application/x-gzip .gz .tgz

    #
##    AddHandler cgi-script .cgi .pl
    # for openwebmail
##    AddHandler cgi-script .pl
#test openwebmail
##AddHandler server-parsed  .html
###AddHandler server-parsed  .pl

</IfModule>



# Virtual hosts
Include /etc/httpd/httpd-vhosts.conf
```

```
# Various default settings
Include /etc/httpd/extra/httpd-default.conf

# Configure mod_proxy_html to understand HTML4/XHTML1
<IfModule proxy_html_module>
Include /etc/httpd/extra/proxy-html.conf
</IfModule>

<IfModule ssl_module>
SSLRandomSeed startup builtin
SSLRandomSeed connect builtin
</IfModule>

# Deal with user agents that deliberately violate open standards
#
<IfModule setenvif_module>
BrowserMatch "MSIE 10.0;" bad_DNT
</IfModule>
<IfModule headers_module>
RequestHeader unset DNT env=bad_DNT
</IfModule>


# Uncomment the following line to enable PHP:
#
Include /etc/httpd/mod_php.conf
```

Links

- http://www.linuxquestions.org/questions/slackware-14/suidperl-in-slack-14-a-4175450139/
- http://openwebmail.org/openwebmail/doc/faq.txt
- http://openwebmail.org/openwebmail/doc/readme.txt
- http://www.unixresources.net/linux/lf/45/archive/00/00/01/69/16969.html
- http://mail.savs.hcc.edu.tw/~chuavv/articles/openwebmail-en.html
- http://search.cpan.org/search?query=CGI&mode=all
- http://svn.apache.org/repos/asf/spamassassin/branches/3.3/INSTALL

Fuentes

- With help of user phenixia2003 from LinuxQuestions.org Forums
- Thanks for editing Eric Hameleers
- Escrito originalmente por John Ciemgals
- Traducido por: Victor 2019/02/14 18:10 (UTC)

howtos, author wisedraco

From:
https://docs.slackware.com/ - **SlackDocs**

Permanent link:
https://docs.slackware.com/es:howtos:network_services:install_openwebmail

Last update: **2019/02/14 18:12 (UTC)**