

Zabbix

Zabbix is an open source network monitoring application capable of monitoring network devices, servers, databases and web services on a wide variety of operating systems.

Website: www.zabbix.com

Prerequisites

- [MySQL](#)
- [httpd](#)

Installation

Zabbix is available at [zabbix_agentd \(SBo\)](#), [zabbix_proxy \(SBo\)](#), [zabbit_server \(SBo\)](#)

1) Create the **zabbix** user and group

```
root@darkstar# groupadd -g 228 zabbix
root@darkstar# useradd -d /dev/null -s /bin/false -u 228 -g 228 zabbix
```

3) Install the necessary version of **Zabbix** from SBOPKG/Slackbuilds

- [zabbix_agentd](#)
- [zabbix_proxy](#)
- [zabbit_server](#)

4) Create the **MySQL** database

4a) On your **MySQL** server, connect with full privileges:

```
root@darkstar# mysql -u root -p
```

4b) Create the zabbix database & user:

```
mysql> create database zabbix character set utf8;
mysql> use mysql;
mysql> grant all on zabbix.* to zabbix@localhost identified by
'<zabbix_password>';
mysql> flush privileges;
mysql> quit
```

4c) On your **Zabbix** server, connect to the new database, create the schema & add initial data:

```
root@darkstar# cd /usr/share/zabbix_server/create
root@darkstar# mysql -u zabbix -p <zabbix_password>
mysql> use zabbix;
mysql> source schema/mysql.sql;
mysql> source data/data.sql;
mysql> source data/images_mysql.sql;
mysql> quit
```

5) Configure PHP:

5a) Zabbix requires some parameters in **/etc/httpd/php.ini** to be altered:

```
post_max_size = 16M           (Default = 8M)
max_execution_time = 300      (Default = 30)
max_input_time = 300          (Default = 60)
date.timezone = America/Chicago (Default = blank)
***NOTE*** the ";" in front of date.timezone MUST be removed
```

5b) Enable PHP in **/etc/httpd/httpd.conf**:

- **ADD:** index.php to the “DirectoryIndex index.html” line.
- **UNCOMMENT:** “Include /etc/httpd/mod_php.conf” line.



After changing the **php.ini** file, you'll need to restart httpd for the changes to have effect:

```
root@darkstar# /etc/rc.d/rc.httpd restart
```

6) Edit the zabbix_server configuration file (**/etc/zabbix/zabbix_server.conf**):

```
DBUser=zabbix           (Default is "root" and it's not a good
idea)
DBPassword=<zabbix_password> (Change as defined above)
```

7) Make **/etc/rc.d/rc.zabbix_server** executable:

```
root@darkstar# chmod +x /etc/rc.d/rc.zabbix_server
```

8) Start the **Zabbix** server

```
root@darkstar# /etc/rc.d/rc.zabbix_server start
```

The **Zabbix** server can be accessed via a web browser at http://your_server/zabbix/

Follow the setup instructions.



Default login is:



USER: Admin
PASS: zabbix

Sources

* Originally written by [arfon](#)
* Contributions by [mfillpot](#) * Contributions by [markand](#)
[howtos](#), [software](#), [zabbix](#), [network monitoring](#), author arfon

From:
<https://docs.slackware.com/> - **SlackDocs**

Permanent link:
<https://docs.slackware.com/howtos:software:zabbix>

Last update: **2019/02/21 12:05 (UTC)**

